


CE MARKING - DECLARATION of PERFORMANCE (DoP)

No. NESSGLAZE LTD: FIRE EXIT DOUBLE DOOR 12/06/2018

Fabricator: NESSGLAZE LTD UNITS 1-4 PARKEND INDUSTRIAL ESTATE; STORNOWAY; ISLE OF LEWIS Post code: HS2 0AN	Installers details to be added where frames sold unglazed	Installer:  Post code: Or Registered No (5):
Window or Door	Door	
System	Total 70	
Style	French Doors (Open Out)	
Application & VACP	Class 1 (Escape Route)	
Authorised Representative	WILLIAM MACRITCHIE	
Notified Body - hEN(4)		
Notified Body - ETA		
Test/certification body	BSI	KM 13358

Essential Characteristics acc. EN 14351-1: 2006 A1:2010

Resistance to Windload(3)	Class 2 (800 Pa)	
Resistance to Water(3)	Class 3A (100 Pa)	
Dangerous substances(1)	As per declaration by component suppliers	
Impact Resistance - doors	NPD	
Load bearing of safety devices(1)	NPD	350N if fitted
Height (Doors only)		
Operation forces (Automatic devices only)	NPD	
Acoustic Performance	NPD	
Thermal transmittance(1) (2) (3)	Minimum requirement (W/m <sup>2</sup> K)	Glazing requirement (W/m <sup>2</sup> K) Warm Edge $\Psi$ 0.04 - Metal $\Psi$ 0.06
	1.8	1.7 - 1.6
Radiation Properties	NPD	
Air Permeability(3)		
Ability to release (Class 1 escape routes only)(1)		
Company Authorised Personnel - Fabricator	Name:	WILLIAM MACRITCHIE
	Company Position:	MANAGING DIRECTOR
	Signature:	
	Date:	12/06/2018
Company Authorised Personnel - Installer	Name:	
	Company Position:	
	Signature:	
	Date:	12/06/2018

Comments/notes:

(1) Threshold values must be entered - No Performance Declared (npd) acceptable for all other Essential Characteristic Values (2) Thermal transmittance declared value dependent on fitting of specified glazing unit by manufacturer or named installer (3) Entry performance values declared where improved results may be available for specific applications (4) Requirement for Notified Body approval of ITI & FPC for Class 1 doors (on escape routes)

Conditions for unglazed frames:

(5) Installers Registered No. assigned by the fabricator. The fabricator must then hold details, on a register, which the installer signs to agree with the terms and conditions to which the declaration refers. It is the installers responsibility to ensure that the whole window conforms to the declared U value or better by sourcing a suitable glazing unit