


CE MARKING - DECLARATION of PERFORMANCE (DoP)

No. **NESSGLAZE LTD: OPEN IN DOOR 05/09/2013**

| | | |
|---|---|--|
| Fabricator: NESSGLAZE LTD UNITS 1-4 PARKEND INDUSTRIAL ESTATE, STORNOWAY, ISLE OF LEWIS Post code: HS2 0AN | Installers details to be added where frames sold unglazed | Installer: Post code: Or Registered No (5): |
| Window or Door | Door | |
| System | Total 70 | |
| Style | Single Door (Open In) | |
| Application & VACP | Class 3 (Non Escape Route) | |
| Authorised Representative | | |
| Notified Body - hEN(4) | | |
| Notified Body - ETA | | |
| Test/certification body | BSI | KM 13358 |

Essential Characteristics acc. EN 14351-1: 2006 A1:2010

| | | |
|--|---|---|
| Resistance to Windload(3) | Class 2 (800 Pa) | |
| Resistance to Water(3) | Class 3A (100 Pa) | |
| Dangerous substances(1) | As per declaration by component suppliers | |
| Impact Resistance - doors | NPD | |
| Load bearing of safety devices(1) | NPD | 350N if fitted |
| Height (Doors only) | | |
| Operation forces (Automatic devices only) | NPD | |
| Acoustic Performance | NPD | |
| Thermal transmittance(1) (2) (3) | Minimum requirement (W/m ² K) | Glazing requirement (W/m ² K) Warm Edge Ψ 0.04 - Metal Ψ 0.06 |
| | 1.8 | 1.7 - 1.6 (or Panel) |
| Radiation Properties | NPD | |
| Air Permeability(3) | Class 1 (150 Pa) | |
| Ability to release (Class 1 escape routes only)(1) | | |
| Company Authorised Personnel - Fabricator | Name: | NORMAN MACRITCHIE |
| | Company Position: | MANAGING DIRECTOR |
| | Signature: |  |
| | Date: | 05/09/2013 |
| Company Authorised Personnel - Installer | Name: | |
| | Company Position: | |
| | Signature: | |
| | Date: | 05/09/2013 |

Comments/notes:

(1) Threshold values must be entered - No Performance Declared (npd) acceptable for all other Essential Characteristic Values. (2) Thermal transmittance declared value dependant on fitting of specified glazing unit by manufacturer or named installer
(3) Entry performance values declared where improved results may be available for specific applications. (4) Requirement for Notified Body approval of ITT & FPC for Class 1 doors (on escape routes)

Conditions for unglazed frames:

(5) Installers Registered No. - assigned by the fabricator. The fabricator must then hold details, on a register, which the installer signs to agree with the terms and conditions to which the declaration refers. It is the installers responsibility to ensure that the whole window conforms to the declared U value or better by sourcing a suitable glazing unit.